

MSDS Report

Report No. (报告编号): MTi241105018-13B1

Date of issue (签发日期): 2024.12.18

Sample Name: Portable Power Station

样品名称: 便携式储能电源

Model:

型号:

AC70P

Applicant: SHENZHEN POWEROAK NEWENER CO., LTD

申请商: 深圳市德兰明海新能源股份有限公司

Address: F19, BLD No.1, Kaidaer, Tongsha Rd No.168, Xili Street, Nanshan,

地址: Shenzhen, China

深圳市南山区西丽街道新围社区同沙路 168 号凯达尔集团中心大厦 1

号楼十九层

Effective date:

生效日期:

2025.01.01





Material Safety Data Sheet

化学品安全技术说明书


Section 1 – Chemical Product and Company Identification 第 1 节 - 化学品和企业标识

No i le 101 HHALE TITTEM IN INC.			
Sample Name:	Portable Power Station		
样品名称	便携式储能电源		
Trade Mark:	BLUETTI		
商标			
Model:	AC70P		
型号	7.070.		
Technical Parameters:	27Ah, 864Wh, 32V		
技术参数	27711, 00 1771, 02 1		
Weight:	About(约):10.56Kg		
重量	About(\$1). 10.30Ng		
Dimension	May(是十萬), T.250.0mm, W.210.0mm, L.210.0mm		
尺寸	Max(最大值): T:250.0mm, W:210.0mm, L:310.0mm		
Manufacturer	Huizhou PowerOak Innovation Co.,Ltd		
制造商	惠州市新明海科技有限公司		
Manufacturer Address	(No.1 Workshop) Longsheng 5th Road. Laoshe Village. Dayawan		
制造商地址	WestZone, Huizhou,Guangdong,China		
	惠州市大亚湾西区老輋村龙盛五路(1号厂房)		
Contact information	Tel: /		
联系方式	1 el. /		
E-mail address	sunxp@poweroak.net		
电子邮件地址	Sunxp@poweroak.net		
Version number:	V1.0		
版本号			
Referenced documents	ISO 11014:2009 Safety data sheet for chemical products		
参考文件	ISO 11014: 2009 化学品安全技术说明书		

Section 2 - Hazards Identification

第2节 - 危害性概述

Preparation hazards and	Not dangerous with normal use. Do not dismantle, open or shred	
classification	battery. Exposure to the ingredients contained within or their	
制剂危害及分类	ingredients products could be harmful.	
	正常使用不危险。请勿拆卸、开启或撕碎电池。暴露于其中的成分或其成分产品可能是有害的。	





Apperance, Color, and Odor	Solid object with no odor, gray.	
外观、颜色和气味 	固体,无气味,灰色	
Primary Route(s) of Exposure 主要暴露途径	These chemicals are contained in a sealed stainless steel enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact. 这些化学物质包含在一个密封的不锈钢外壳中。只有当电池被机械地、热地或电地滥用到危及外壳的程度时,才有暴露的危险。如果出现这种情况,吸入、摄入、眼睛接触和皮肤接触都可能暴露在电解质溶液中。	
Potential Health Effects: 潜在健康影响:	ACUTE (short term): see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.	
	急性(短期):请参阅第8节的暴露控制,如果电池已经破裂,电池内的电解质溶液将是腐蚀性的,并可能导致烧伤。	
	Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation.	
	吸入:从密封电池中吸入物质不是预期的接触途径。电池破裂产生的蒸汽或薄雾可能引起呼吸道刺激。	
	Ingestion: Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.	
	摄入:从密封电池中吸收物质不是预期的暴露途径。吞下打开的电池会引起口腔、食道和胃肠道的严重化学灼伤。	
	Skin: Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin.	
	皮肤:电池与皮肤接触不会造成任何伤害。皮肤接触打开的电池内容物可能导致严重的刺激或烧伤皮肤。	
	Eye: Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye.	
	眼睛:电池与眼睛接触不会造成任何伤害。与打开的电池的内容物进行接触会对眼睛造成严重的刺激或灼伤。	
	CHRONIC (long term): see Section 11 for additional toxicological data 慢性(长期): 有关其他毒理学数据,请参阅第 11 节	




Medical Conditions Aggravated	Not applicable
by Exposure	不适用
因暴露而加重的健康状况	
Reported as carcinogen	Not applicable
报告为致癌物质	不适用

Section 3 – Composition/Information on Ingredients 第 3 节-成分/组成信息

Battery is a mixture.

电池是一种混合物

Chemical composition	Chemical Formula	Concentration(%)	CAS No
化学成分	化学式	浓度(%)	CAS 号
Lithium iron phosphate 磷酸铁锂	LiFePO ₄	34	15365-14-7
Graphite 石墨	С	20	7782-42-5
Aluminium 铝	Al	4	7429-90-5
Copper 铜	Cu	7	7440-50-8
Polyvinylidene fluoride 聚偏氟乙烯	C ₂ H ₂ F ₂	1	24937-79-9
Carboxymethylcellulose 羧甲基纤维素	C ₈ H ₁₆ O ₈	0.2	9000-11-7
Styrene Butadiene Rubber 丁苯橡胶	C ₃₆ H ₄₂ X ₂	0.5	9003-55-8
Polypropylene 聚丙烯	(C ₃ H ₆) _n	2.5	9003-07-0
Lithium hexafluorophosphate 六氟磷酸锂	LiPF ₆	2	21324-40-3
Ethylene carbonate 碳酸乙烯酯	C ₃ H ₄ O ₃	2	96-49-1
Ethyl methyl carbonate 碳酸甲酯乙酯	C ₄ H ₈ O ₃	1	623-53-0
Dimethyl carbonate 碳酸二甲酯	C ₃ H ₆ O ₃	8	616-38-6
Nickel 镍	Ni	0.1	7440-02-0
Iron 铁	Fe	17	7439-89-6





Carbon black 碳黑	С	0.5	1333-86-4
Carbon Nanotubes 碳纳米管	С	0.2	308068-56-6

Labeling according to EC directives.

根据欧共体指令进行标识

No symbol and risk phrase are required.

不需要符号和风险短语


Note: CAS number is Chemical Abstract Service Registry Number. N/A=Not apply

注:CAS 编号为化学文摘服务注册编号。N/A=不适用

Section 4 - First-aid Measures

第4节-急救措施

Inhalation 吸入	If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice. 如果吸入打开的电池的内容物,清除污染源或转移受害者到新鲜空气。或者获得医学建议。
Skin contact 皮肤接触	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard. 如果皮肤接触到打开的电池内容物发生,尽快清除污染的衣服,鞋子和皮具。立即用温水冲洗至少 30 分钟。如果刺激或疼痛持续,请就医。彻底清洁衣物、鞋及皮具,然后再使用或弃置。
Eye contact 眼睛接触	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility. 如果眼睛接触到打开的电池的内容物,立即用温水冲洗污染的眼睛,同时保持眼睑打开至少 30 分钟。一旦可用,就可以使用中性盐水溶液。如有需要,在送往急救中心的途中继续冲洗。注意不要将受污染的水冲洗到未受影响的眼睛或脸上。迅速将伤者送往急救中心。





Ingestion

摄入

If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. Do not induce vomiting. Have victim drink 60 to 240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.

如果摄入打开的电池的内容物,如果受害者迅速失去意识,或者无意识或抽搐,切勿通过口腔给予任何东西。 让受害者用水彻底冲洗口腔。 不要催吐。 让受害者饮用 60 至 240 毫升(2-8 盎司)的水。 如果呕吐自然发生,让受害者向前倾,以降低误吸风险。 让受害者再次用水冲洗口腔。 迅速将受害者运送到急救室。

Section 5 – Fire-fighting Measures

第5节-消防措施

Flammable Properties 易燃的特性	In the event that this battery has been ruptured, the electrolyte solution contain within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials. 如果电池破裂,电池内的电解质溶液是易燃的。与任何密封容器一样,电池在过热时可能会破裂;这可能导致易燃或腐蚀性物质的释放。	
Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.	
适合的灭火剂	使用适合燃烧材料的灭火剂	
Unsuitable extinguishing Media	Not available	
不合适的灭火剂	不适用	
Explosion Data	Sensitivity to Mechanical Impact: This may result in rupture in	
爆炸的数据	extreme cases	
	对机械冲击的敏感性: 在极端情况下可能会导致破裂	
	Sensitivity to Static Discharge: Not Applicable	
	对静电放电敏感:不适用	
Specific Hazards arising from the	Fires involving battery can be controlled with water. When water is	
chemical	used, however, hydrogen gas may evolve. In a confined space,	
该化学品产生的特定危害	hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to extinguish the fire	
	涉及电池的火灾可以用水控制。 然而,当使用水时,氢气可能会进化。在密闭空间中,氢气可以形成爆炸性混合物。 在这种情况下,建议使用窒息剂扑灭火灾	



Protective Equipment and precautions for firefighters 消防人员的防护设备和预防措施	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear. 如遇火警,应立即疏散,并在安全距离内灭火。穿戴压力要求,自给式呼吸器和全套防护装备。从受保护的地点或安全距离灭火。使用NIOSH/MSHA认可的全脸自给式呼吸器(SCBA)和全套防护装备。	
NFPA	Health: 0 Flammability: 0 Instability: 0 健康:0易燃性:0不稳定性:0	

Section 6 – Accidental Release Measures 第 6 节-泄漏应急措施

Personal Precautions, protective equipment, and emergency procedures 个人预防措施,防护设备和应急程序	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8. 在清理完成之前限制进入该区域。 请勿触摸溢出的材料。 如第8节所述,穿戴足够的个人防护装备。		
Environmental Precautions 环境保护措施	Prevent material from contaminating soil and from entering sewers or waterways. 防止材料污染土壤并进入下水道或水道。		
Methods and materials for Containment 遏制的方法和材料	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately. 如果安全,请停止泄漏。 用干沙或泥土包含溢出的液体。 立即清理溢出物。		
Methods and materials for cleaning up 清理方法和材料	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal. 用惰性吸附剂(干沙或土)吸收溢出的物质。将受污染的吸收剂舀入可接受的废物容器中。收集所有受污染的吸附剂,并按第13条的指示处置。用洗涤剂和水擦洗该区域;收集所有受污染的洗涤水,以便妥善处理。		



Section 7 - Handling and Storage

第7节-操作处理和储存

Handling	Don't handling battery with metalwork. Do not open, dissemble, crush
操作处理	or burn battery. Ensure good ventilation/ exhaustion at the workplace.
	不要用金属制品处理电池。请勿打开、掩饰、压碎或烧毁电池。确保 工作场所有良好的通风。
	Prevent formation of dust.
	防止灰尘的形成。
	Information about protection against explosions and fires: Keep ignition sources away-Do not smoke.
	关于防爆和防火的信息:远离火源——不要吸烟。
Storage	If the battery are subject to storage for such a long term as more than
存储	6 months, it is recommended to recharge the battery periodically.
	如果电池的存储时间超过6个月,建议定期对电池进行充电。
	Storage Temperature
	储存温度
	Short period less than 3 months: 5℃~+40℃
	短期不到 3 个月:5℃~+40℃
	Short period less than 1 year: 10 ℃~+35 ℃
	短期不到 1 年: 10℃~+ 35℃
	Humidity: 60±25%RH
	湿度: 60±25%RH
	Do not storage battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
	请勿将电池随意存放在可能相互短路或被其他金属物体短路的盒子或抽屉中。
	Do not expose battery on heat or fire. Avoid storage in direct sunlight.Do not store together with oxidizing and acidic materials.Do not store together with oxidizing and acidic materials.Keep container tightly sealed.
	不要将电池暴露在高温或火灾中。避免在阳光直射下存放。不要与氧 化和酸性物质一起储存。不要与氧化和酸性物质一起储存。保持容器 密封。



Section 8– Exposure Controls and Personal Protection 第8节-接触控制和个人防护


Engineering Controls	Use local exhaust ventilation or other engineering controls to control		
工程控制方法	sources of dust, mist, fumes and vapor.		
	使用当地的排气通风或其他工程控制来控制灰尘,薄雾,烟雾和蒸汽的来源。		
	Keep away from heat and open flame. Store in a cool, dry place.		
	远离热源和明火。 存放在阴凉,干燥的地方。		
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions.		
个人防护设备	呼吸保护:正常情况下不需要。		
	Skin and body Protection: Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery.		
	皮肤和身体保护:在正常情况下不需要,如果处理打开或泄漏的电池, 请戴上氯丁橡胶或丁腈橡胶手套。		
	Hand protection: Wear neoprene or natural rubber material gloves if handling an open or leaking battery.		
	手部防护:如果处理打开或泄漏的电池,请戴上氯丁橡胶或天然橡胶材料手套。		
	Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.		
	眼睛防护:在正常条件下不需要,如果处理打开或泄漏的电池,请戴上安全眼镜。		
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the		
其他防护设备	immediate work area.		
	在工作区域附近有一个安全的淋浴喷头和洗眼喷头。		
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good		
卫生措施	housekeeping. 不要在工作区域进食,饮水或吸烟。 保持良好的内务管理。		

Section 9 - Physical and Chemical Properties

第9节 - 物理和化学特性

Form: Solid Physical State 形态: 固体

电话(Tel):0755-88850135-1439 手机(Mobile): 131-4343-1439(Wechat same number) 网址(Web):http://www.mtitest.cn 邮箱(E-mail): mti@51mti.com 地址: 广东省深圳市宝安区福海街道新和社区福海大道新兴工业园二区7号101 Address: Room 101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Road, Xinhe, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China Q/MTI-QP-12-FB004 Ver./Rev.: A0 Page 9 of Ver./Rev.: A0 Page 9 of 14





自燃温度

物理状态 Color: gray 颜色: 灰色 Odour: If leaking, smells of medical ether. 气味:泄漏时,有醚的气味。 Change in condition: 变化的条件: pH, with indication of the Not applicable concentration 无可用数据 pH,指示浓度 Melting point/freezing point Not available. 熔点/凝固点 无可用数据 Boiling Point, initial boiling point Not available. and Boiling range: 无可用数据 沸点、初始沸点及沸点范围: Flash Point Not available. 闪点 无可用数据 Upper/lower flammability or Not available. explosive limits 无可用数据 上/下可燃性或爆炸极限 Vapor Pressure: Not applicable 蒸汽压力: 无可用数据 Vapor Density: (Air = 1) Not applicable 蒸汽密度:(空气=1) 无可用数据 Density/relative density Not available. 密度/相对密度 无可用数据 Solubility in Water: Insoluble 水中溶解度: 无可用数据 n-octanol/water partition Not available. coefficient 无可用数据 n-octanol /wate分配系数 Not available. Auto-ignition temperature

无可用数据



Decomposition temperature	Not available.
分解温度	无可用数据
Odout threshold	Not available.
气味阈值	无可用数据
Evaporation rate	Not available.
蒸发率	无可用数据
Flammability (soil, gas)	Not available.
易燃性(固体、气体)	无可用数据
Viscosity	Not applicable
粘性	无可用数据

Section 10 - Stability and Reactivity

第10节-稳定性和反应性

Stability	The product is stable under normal conditions.
稳定性	该产品在正常条件下稳定。
Conditions to Avoid (e.g. static discharge, shock or vibration) 应避免的情况(例如静电放电、冲击或振动)	Do not subject battery to mechanical shock. 不要让电池受到机械冲击。 Vibration encoutered during transportation does not cause leakage, fire or explosion. 运输过程中产生的振动不会引起泄漏、火灾或爆炸。 Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse. 不要拆卸、压碎、短路或安装极性不正确。避免机械或电气滥用。
Incompatible Materials 不相容的材料 Hazardous Decomposition	Not Available 无可用数据 This material may release toxic fumes if burned or exposed to fire
Products 危险的分解产物	如果燃烧或暴露在火中,该材料可能释放有毒烟雾
Possibility of Hazardous Reaction 危险反应的可能性	Not Available 无可用数据



Section 11 - Toxicological Information

第11节 - 毒理学信息

Irritation 刺激性	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur. 只有当细胞被机械地、热地或电地滥用到危及外壳的程度时,才会出现刺激的危险。如果出现这种情况,可能会对皮肤、眼睛和呼吸道造成刺激。
Sensitization	Not Available
致敏	无可用数据
Neurological Effects	Not Available
神经系统的影响	无可用数据
Teratogenicity	Not Available
致畸性	无可用数据
Reproductive Toxicity	Not Available
生殖毒性	无可用数据
Mutagenicity (Genetic Effects)	Not Available
致突变性 (遗传效应)	无可用数据
Toxicologically Synergistic	Not Available
Materials	无可用数据
毒理学协同材料	

Section 12 - Ecological Information

第12节-生态学信息

General note:	Water hazard class 1(Self-assessment): slightly hazardous for water.
一般说明:	水危害等级 1 (自我评估): 对水有轻微危害。
	Do not allow undiluted product or large quantities of it to reach
	ground water, water course or sewage system.
	不允许未稀释的产品或大量产品进入地下水、河道或污水系统。
Anticipated behavior of a chemical	Not Available
product in environment/possible	无可用数据
environmental impace/ecotoxicity	
化学产品在环境中的预期行为/可能 的环境影响/生态毒性	



Mobility in soil	Not Available
土壤中的流动性	无可用数据
Persistence and Degradability	Not Available
持久性和降级性	无可用数据
Bioaccumulation potential	Not Available
生物体内积累的可能性	无可用数据
Other Adverse Effects	Not Available
其他不利影响	无可用数据

Section 13 - Disposal Considerations

第13节 - 废弃处置

Product disposal recommendation: Observe local, state and federal laws and regulations.

Attention for Waste Treatment: Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

产品处置建议: 遵守当地、州和联邦法律法规。

废弃注意事项: 废电池不能被当作普通垃圾。不能扔进火中或置于高温下。不能解体,刺穿,破碎或类似的 处理。最好的处理办法是回收利用。

Section 14 – Transport Information

第 14 节-运输资料

For the international transport of lithium batteries, they must comply with these regulations: the International Maritime Dangerous Goods (IMDG) Code by International Maritime Organization (IMO), Dangerous Goods Regulations (DGR) by International Air Transport Association (IATA) and Technical Instructions for the Safe Transport of Dangerous Goods by Air by International Civil Aviation Organization (ICAO). These regulations are based on the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.

对于锂电池的国际运输,它们必须遵守这些规定:国际海事组织(IMO)的国际海运危险货物(IMDG)规则,国际航空运输协会(IATA)的危险货物规则(DGR)和技术细则 国际民用航空组织(ICAO)通过航空安全运输危险货物。 这些法规以"联合国关于危险货物运输的建议书,试验和标准手册"为基础。

Lithium batteries which meet the requirements of UN38.3 (UN Manual of Tests and Criteria, Part III, subsection 38.3) could be transported by air and by sea as ordinary goods, otherwise should be transported according to Class 9, Packing Group II hazardous goods.

符合UN38.3(联合国试验和标准手册,第III部分,第38.3小节)要求的锂电池可作为普通货物通过空运和海运运输,否则应按第9类包装II类危险货物运输

International regulations for transport Sea IMDG CODE (Amdt.42-24): Special provision 188.

《国际海运IMDG规则》(Amdt.42-24):特别条款188。

ICAO / IATA: Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI



Report No.:MTi241105018-13B1

or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IA appropriate of IATA DGR 66th (2025 Edition) for transportation.

国际民间航空组织/国际航空运输协会:货物可按照国际民用航空组织(ICAO), TI或国际航空运输协会(IATA), DGR 66th(2025版)包装说明 (PI) 965 Section IA相关规定进行空运。

UN number: UN3480

联合国危险货物编号: UN3480

UN Proper shipping name: Lithium ion batteries

联合国运输名称: 锂离子电池

Transport hazard classification: Class 9 lithium battery hazard

联合国危险运输危险级别:第九类锂电池危险品 Packing group (if applicable): Packing Group II

包装组(如果可能): II级包装 Marine pollutant (Yes/No): No

海洋污染物(是/否): 否

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): No information available.

散装运输(根据《73/78 防污公约》附件二及《国际散化规则》): 无可用资料

Special precautions: No information available.

特别预防措施: 无可用资料

Section 15 - Regulatory Information

第15节-法规信息

OSHA hazard communication standard (29 CFR 1910.1200)

职业安全与健康管理局危险通讯标准(29 CFR 1910.1200)

Hazardous 有害的	√ Non-hazardous 无害的

Section 16 - Other Information

第16节-其他信息

The information above is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. We makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall we be liable for Any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however arising from using the above information.

上述信息被认为是正确的,但并不意味着包含所有内容,仅用作指南。 对于此类信息,我们不保证适销性或任何其他明示或暗示的保证,并且我们不承担因使用此类信息而产生的任何责任。 用户应进行自己的调查,以确定信息是否适合其特定用途。 我们绝不对任何第三方的任何索赔,损失或损害赔偿或利润损失或任何特殊,间接,偶然,后果性或示范性损害赔偿承担责任,无论这些损害是否因使用上述信息而产生。

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

此处包含的数据/信息已经过审核和批准,因为本文档不包含出口管制信息。

End of Report 报告结束
